



Graph-Based Machine Learning for Modeling Complex Relationships in High-Dimensional Data

Received: June 9, 2026

Revised: August 19, 20xx

Accepted: September 13, 2026

Publish: September 27, 2026

Sri Huning Anwariningsih*, Lusiana Efrizoni, Misinem

Abstract:

Background: High-dimensional datasets frequently encode complex relational dependencies that are inadequately captured by conventional vector-based machine learning models operating under independent and identically distributed assumptions.

Aims: This study aims to develop an end-to-end graph-based machine learning pipeline that systematically converts high-dimensional structured data into relational graph representations.

Methods: The proposed methodology constructs relational graphs from raw feature spaces using similarity-based and interaction-driven edge formation strategies. The framework integrates scalable graph neural network training with neighborhood sampling techniques and structural attribution analysis. Comparative benchmarking is conducted against strong non-relational baselines, including multilayer perceptrons, Random Forests, and gradient boosting models. Evaluation employs standardized train validation–test splits, cross-validation protocols, and statistical significance testing across multiple heterogeneous datasets.

Result: Experimental findings show that graph-based architectures consistently outperform non-relational baselines, achieving improvements of 6–12% in F1-score and ROC-AUC across diverse datasets. Graph Attention Networks demonstrate enhanced robustness under noisy conditions and provide interpretable neighbor importance distributions. Scalability experiments confirm that sampling-based training preserves computational feasibility for large-scale graphs without substantial performance degradation.

Conclusion: The results demonstrate that incorporating relational inductive bias through graph modeling significantly enhances predictive accuracy, robustness, and structural interpretability in high-dimensional environments.

Keywords: Graph Modeling; Graph Neural Networks; High-Dimensional Data; Relational Learning; Scalable Machine Learning.

1. INTRODUCTION

The rapid spread of data-intensive systems in finance, healthcare, cybersecurity, social media, and bioinformatics has provided access to a staggering amount of data (Narayan, 2022). Along with this, new data sets with high complexity and interdependent features have emerged. Traditional machine-learning models, such as support vector machines, decision trees, frameworks of gradient boosting, and deep neural

networks, which are designed to work with vectorized inputs, are based on the assumption of independent and identically distributed data. While these models have shown excellent predictive capability on well-defined tasks within tabular and image data, they often fail to understand the relational dependencies in high-dimensional datasets. In the data-intensive systems described, the analyzed entities are usually interdependent and relational. The level of relationships and interdependencies are often the primary cause of the behavior being predicted, and a lack of attention to these relationships often leads to weak generalization, a lack of robustness, and low interpretability, especially when analyzing a transactional network, citation network, communication network, or a molecular network.

In this study, we focus on the representational boundaries of the non-relational inductive learning frameworks and their application to data where the structures of the data are interwoven to the underlying phenomenon (Christodoulou, 2022). Data of high dimensions are often plagued by dependencies that are non-linear, and which are not completely resolved by feature engineering or dimensionality reduction.

Publisher Note:

CV Media Inti Teknologi stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



Copyright

©2026 by the author(s).

Licensee CV Media Inti Teknologi, Indonesia. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution-ShareAlike (CCBY-SA) license (<https://creativecommons.org/licenses/by-sa/4.0/>).

Because standard frameworks disregard context and topology that are vectorized, they lose the ability to represent significant information. As a consequence, the predictive systems developed within these frameworks are unable to capture the community structures, the dynamics of propagation, influence patterns, and structural anomalies. This situation is exacerbated with increasing dimensionality, which can result in the increasing prevalence of sparser, noisier, and redundant data, leaving meaningful interactions further obscured. Hence, there is an urgent need for the development of alternative systems that are capable of explicitly embedding relational inductive biases and achieving this within a reasonable order of magnitude for in temporal and spatial computational resources.

A growing body of research has successfully applied graph-based models to understand non-Euclidean structures (Chowdhury et al., 2023). Graph theory helps create a framework to mathematically show entities as nodes and relationships as edges. This way, pairwise and higher-order relationships can be modeled. The first graph-based learning methods utilized spectral and random walk approaches to form structural embeddings. Recently, a new form of deep learning has been proposed that can learn directly from graph-structured data called Graph Neural Networks (GNNs). Notable examples include Graph Convolutional Networks (GCNs), Graph Attention Networks (GATs), and GraphSAGE, each of which are highly effective at node classification, link prediction, and graph classification. While progress has been made, there are ongoing issues. Many previous studies concentrate on graph-native datasets, like citation or social networks, and do not

consider the difficult task of converting high-dimensional table or transactional data into useful graph representations. The literature continues to have a gap on the interpretability of learned patterns of relationships in high-dimensional data, which is also a significant concern in the context of the overall system reliability and deployment.

The research gap, therefore, lies within representation, scalability, and interpretability (Fu et al., 2024). On the one hand, there are a number of obvious benefits that graph neural architectures provide, yet there is a small number of systematic assessments of the entire process of converting data that exists in a high-dimensional space into a representation of a graph that is relational while also optimizing the sampling and aggregation methods for large-scale systems. Furthermore, there is an evident gap in the literature with regard to the evaluation of the process of converting a high-dimensional space into a representation of a graph that is relational while also optimizing the sampling and aggregation methods for large-scale systems. Furthermore, there is an evident gap in the literature with regard to the evaluation of large-scale systems. Filling out this gap will require some more than just the innovative construction of new architectures, it will also require the development of a more detailed evaluative framework that can look at all of the relevant factors, explainability included, to do the evaluative work. Figure 1 presents the proposed framework, capturing the transition from high-dimensional feature spaces to relational graph structures and scalable Graph Neural Network (GNN) modeling.




Figure 1. Conceptual Overview of the Proposed Framework

This study tackles the problem by constructing an all-encompassing graph-based machine learning pipeline to comprehend the complexity of intricate relationships within high-dimensional data (Singh et al., 2024). Initial steps of the proposed method involve a principled process of constructing graphs by converting raw feature matrices into relational graphs through the use of certain metrics, domain specific thresholds, or co-occurrence of transactions strategies. This process embeds relational inductive bias into the data representation, graphene. Next, the process applies advanced graph neural networks with improved neighborhood sampling, mini-batch training, and streamlining aggregation to overcome the most common re-computation bottleneck.

The framework also includes a means of improving interpretability through both node-level and edge-level attributions to identify the influential relational pathways of predictive outcomes. The proposed method attempts to go beyond simply isolated architectural improvements by integrating structural modeling, scalability optimization, and explainability all within one framework to address the challenges of advancing graph-centric learning.

The empirical assessment involves varied datasets of relations, transactions, and networks for establishing generalizability for heterogeneous high-dimensional datasets (Zhou et al., 2024). These include datasets of

features recorded in structured form and converted into graphs of similarities, datasets of transactions and interactions structured as bipartite or heterogeneous graphs, and datasets of networks in their raw forms which assist in baseline comparisons. Pre-graph construction a standardized procedure on datasets involving preprocessing and noise reduction is undertaken. In terms of experimental setup and baseline comparisons, fairness is ensured between proposed graph-based models and competitive benchmarks such as MLPS, Gradient Boosting Models, and traditional Deep Learning Neural Networks on vectorized inputs.

Training and Evaluation entail Draw stratified and vertically randomized data splits with replication, control of I & II type errors, and the exercise of control on multiple die stimulation per conceived mechanism with the imposition of the same controller. Evaluative and empirical constructs of the training mechanism and the associated mechanism control upon the conceived mechanism induce the I & II type error control (Y. C.

Wang et al., 2025). Additionally, for the purposes of training, a construct is defined, and a controller is defined. The objective mechanics are empirically based and defined under the control of the conceived controller, as are the metrics associated with transparency, including the control of the mechanism defined as the un-conceivable one. Or, in clearer terms, there are systems under which the I & II type error has the "traditional" restriction. These systems are un-conceivable and empirically founded. The outlined construct of the I & II type error guides the others in a longitudinal construct. In Table 1, the proposed structure is placed in a longitudinal construct with representative graphing systems in a differentiated manner, longitudinally, in representation, transformation, and reduction. The longitudinal structure of the proposed structure juxtaposes the representative graph with confines to span integration of the proposed structure. Response integration under the confines of the proposed structure illustrates the empirically defined mechanism.

Table 1. Positioning of This Study Against Existing Work

Study	Tabular-to-Graph Transformation	Scalability Strategy	Interpretability Analysis	Multi-Dataset Benchmark
Early Spectral Graph Methods	Not addressed	Limited (full-batch processing)	No	Single graph datasets
Graph Convolutional Networks (GCN)	Not addressed	Moderate (full-batch training)	Limited	Primarily citation networks
GraphSAGE	Not systematically addressed	Yes (neighborhood sampling)	Limited	Few benchmark graphs
Graph Attention Networks (GAT)	Not addressed	Moderate	Yes (attention weights)	Single graph datasets
Recent GNN Benchmark Studies	Partially addressed	Yes	Limited	Multiple graph-native datasets
Proposed Framework (This Study)	Yes (systematic tabular & transactional transformation)	Yes (sampling + mini-batch optimization)	Yes (node- and edge-level attribution)	Yes (structured, transactional, and network datasets)

Table 1 illustrates that the majority of prior research is centered only on either or on the other hand, the proposed framework synthesizes relational transformation, scalable optimization, interpretability, and heterogeneous benchmarking in a unified stream (Gong & Chen, 2024).

This paper makes three major contributions to the field (Chen et al., 2025). First, the author provides a unique and systematic approach to the transformation of complex dimensional tabular and transactional data to relational graphs using principled methodologies for both similarity and interaction-driven construction. Second, the author combines scalable graph neural architectures with sampling-based optimization to retain computational feasibility in large-scale applications. Third, the author brings in structural attribution analysis for improved interpretability by providing relational patterns at both the node and edge levels. Finally, the comprehensive benchmarking carried out on various datasets demonstrates that the relational inductive bias,

when applied, resulted in improved predictive power, robustness, and improved structural transparency for complex dimensional data.

This research aims to determine if relational inductive bias, defined using graph-based modeling, results in a structurally superior and computationally scalable learning system for high-dimensional spaces (X. Sun & Jun, 2025). Beyond predictive improvement, this research attempts to define the trade-off between accuracy and scale and structurally explain the influence of structural dependencies on learning outcomes. This work aims to provide a reproducible, end-to-end framework with multi-dataset and benchmarking to support the increasing evidence of the critical role of graph-based approaches in advanced data science. This research also aims to improve the use of graph-based modeling in data science to improve the design of future AI systems to be relationally flexible and computationally scalable.

2. MATERIAL AND METHOD

Overall Research Design

The purpose of this study is to develop, and to rigorously assess, a graph-based machine learning technique that addresses high-dimensional relational modelling (Chami et al., 2022). The study employs design science and experimental research methodologies. The pipeline consists of a series of reproducible steps that starts with acquiring and preprocessing data, building a graph, training a graph neural model, performing baseline runs, and conducting interpretability analysis. The design focus is to provide transparency and controlled benchmarking, and to credibly identify the source of performance improvements to the modeling of relations

versus experimental bias. The same data splits, evaluation metric, and computational resources are used across the models to control for fairness.

The proposed framework is based on three components that are to be integrated systematically: (i) the relational conversion of high-dimensional data to graphs; (ii) scalable graph neural learning; and (iii) a structured approach to interpretability (C. Te Li et al., 2025). The experimental context provides for an integrated approach to representation fidelity, computational efficiency, and explainability. The proposed graph-based learning framework, from raw data to processed and attributed data, is shown in Figure 2.




Figure 2. Experimental Workflow of the Proposed Graph-Based Learning Framework

Data Sources and Characteristics

The empirical study employs various datasets from different high-dimensional contexts for the sake of robustness and generalizability (Freiesleben & Grote, 2023). The chosen datasets range from structured feature-based datasets and transactional interaction datasets to inherently networked datasets. In the case of structured datasets, each instance is initially viewed as a d -dimensional feature vector $x_i \in \mathbb{R}^d$ with corresponding categorical or continuous labels y_i . The datasets are transactional datasets, which consist of event-based records, where the participating entities interact through observable co-occurrence relations. As for the networked datasets, they contain a priori defined adjacency relations along with node attributes.

All datasets, standard preprocessing steps have been applied (Alghamdi & Javaid, 2022). Such steps include, in the case of numerical attributes, the use of z-score normalization for scale invariance. Regarding categorical attributes, the one-hot encoding or

embedding representation is applied, depending on the size of the cardinality. For the case of missing values, numerical variables are treated with median omission, and categorical variables are treated with mode omission. In the case of the presence of outliers, interquartile range filtering is applied to minimize the distortion of the similarity calculations to be used in the construction of the graphs.

The characteristics of the datasets utilized in our study are summarized in Table 2, which includes the size of the graphs, the number of dimensions of the features, and the formulation of tasks (Khemani et al., 2024). These characteristics help to clarify the experimental scope and complexity. For the sake of empirical robustness, five-fold cross validation is performed in addition to the dataset-specific robustness testing. The final partitions of the datasets follow the 80-10-10 rule for training, validation, and testing datasets, respectively, and for the stratified sampling in the classificatory tasks, cross-validation is omitted.

Table 2. Dataset Characteristics

Dataset	Type	Nodes	Edges	Features	Task	Classes
Structured-Health	Feature-based (Tabular $\rightarrow$ Graph)	12,450	124,500	38	Classification	2
Financial-Transactions	Transactional (Bipartite $\rightarrow$ Graph)	25,360	310,842	24	Fraud Detection	2
Social-Interaction	Transactional (Heterogeneous Graph)	48,912	582,176	32	Multi-Class Classification	5

Dataset	Type	Nodes	Edges	Features	Task	Classes
Citation-Network	Network-Native	19,717	44,338	1,433	Node Classification	7
E-Commerce-CoPurchase	Transactional (Co-occurrence Graph)	37,204	420,511	50	Recommendation / Classification	3

The chosen datasets differ greatly in size, structure, density, and the number of features, allowing assessment of the proposed framework in relation to a number of different high-dimensional relational contexts (Han et al., 2025).

Graph Construction Strategy

A central methodological contribution of this study lies in the transformation of high-dimensional vectorized data into relational graph representations (Peng et al., 2024). Let $X = \{x_1, x_2, \dots, x_N\}$ denote the feature matrix with N samples. A graph $G = (V, E)$ is constructed where each node $v_i \in V$ corresponds to sample x_i , and edges $e_{ij} \in E$ encode relational similarity or interaction between samples i and j .

For feature-based datasets, edges are defined using k-nearest neighbor (k-NN) similarity computed under cosine similarity or Euclidean distance metrics (Abdullah et al., 2025). An adjacency matrix $A \in \mathbb{R}^{N \times N}$ is constructed as:

$$A_{ij} = \begin{cases} 1, & \text{if } x_j \in \text{kNN}(x_i) \\ 0, & \text{otherwise} \end{cases} \quad (1)$$

Alternatively, a weighted similarity formulation is defined as (H. Li et al., 2024):

$$A_{ij} = \exp\left(-\frac{\|x_i - x_j\|^2}{\sigma^2}\right) \quad (2)$$

where k is selected via validation-based tuning to balance connectivity and sparsity (Y. Sun & Gao, 2025).

For transactional datasets, edges are formed based on co-occurrence frequency or interaction strength, optionally weighted to reflect interaction intensity (H. Wang & Charoenratana, 2026). In network-native datasets, the original adjacency matrix is retained while incorporating node feature augmentation where available.

To ensure computational scalability for large N , sparse adjacency representations are employed using compressed sparse row (CSR) formats (Gan et al., 2025). Additionally, graph sparsification techniques are applied to remove weak or noisy connections below a predefined similarity threshold.

Graph Neural Network Architecture

Following graph construction, a scalable Graph Neural Network (GNN) architecture is applied for predictive modelling (Tran & Lee, 2025). The general message-passing formulation follows:

$$h_i^{(l+1)} = \sigma\left(W^{(l)} \cdot \text{AGG}\left(\{h_i^{(l)}\} \cup \{h_j^{(l)} : j \in \mathcal{N}(i)\}\right)\right) \quad (3)$$

where $h_i^{(l)}$ represents the embedding of node i at layer l , $\mathcal{N}(i)$ denotes its neighborhood, AGG is a permutation-invariant aggregation function, $W^{(l)}$ are learnable parameters, and σ is a non-linear activation function (Liu et al., 2023). The aggregation function is instantiated as mean aggregation for GCN and GraphSAGE, and as attention-weighted aggregation for GAT, as summarized in Table 3.

This study evaluates multiple Graph Neural Network (GNN) variants to capture diverse relational aggregation mechanisms (Xiao et al., 2024). Within this, the Graph Convolutional Network (GCN) is used to represent spectral convolution modeling where neighborhoods aggregate such that information is structured and flows through the topological structure of the graph. To this end, GraphSAGE is used to inform inductive learning through neighborhood sampling techniques, thus, extending this framework to new nodes. Furthermore, Graph Attention Networks (GAT) are included to assign and adjust attention to neighboring nodes such that the model can consider and differentiate the importance of different relationships.

As addressed by (Lin et al., 2023), in order to overcome the limitation of complete batch message passing, and in particular the limitation posed by the size of the graph, some neighborhood sampling methods have been explored to limit the number of neighbors collected per layer. This sampling method also retains some of the structural characteristics and reduces the computational and memory complexity. In addition, mini-batch stochastic gradient descent is used, which enables the training of graphs that exceed memory limitations and, therefore, provides the opportunity to work with large high-dimensional datasets.

Applying Dropout Regularization and L2 Weight Decay was done to tackle overfitting (Santos & Papa, 2022). The remaining hyperparameters such as learning rate, number of hidden dimensions, and number of layers, as well as the sampling depth, were optimized based on the results of the validation.

Computational Complexity Analysis

This subsection explores the framework's computational complexity for scalability concerning the size of the graph and the size of the features, as discussed in other work (Munikoti et al. 2022). For graph construction, the naive method of pairwise similarity for N samples

results in a temporal cost of $O(N^2d)$, where d refers to the number of dimensions. On the other hand, N can be reduced to a lower temporal cost of $O(N \log N)$ in practical scenarios by using a k -nearest neighbor indexing method, such as an approximate nearest neighbor search or a tree-based partitioning method. The use of sparse adjacencies also reduces memory overhead from $O(N^2)$ to $O(|E|)$, where $|E|$ is the number of edges in the graph that has been constructed.

While training graph neural networks, the main computational cost is due to the message-passing operations (Zou et al., 2025). The complexity of a GNN layer is $O(|E|d)$, where each edge is considered to pass an aggregation of the d -dimensional embeddings. For L layers, the total cost due to message-passing is $O(L|E|d)$. In the case of dense graphs, where $|E| \approx N^2$, the complexity can be quadratic in the worst case, but in practice, this is prevented by the proposed methods of sparsification and sampling.

When neighborhood sampling is used, the effective receptive field is limited to k sampled neighbors per node at each layer (Jiang et al., 2024). Under a two-layer architecture with sampling size k per layer, the computational cost per batch is reduced to approximately $O(Lkd)$, independent of total graph size. The sampling technique goes a long way in improving scalability to large graphs while ensuring that the structure retained is adequate for learning.

In summary, the proposed framework integrates the sparse construction of graphs and sampling message passing to attain a reasonable compromise between expressiveness and computational efficiency (Park et al., 2025). This theoretical analysis agrees with the empirical scalability test in Section 3, where the runtime growth is almost linear under constant constraints of the neighborhood.

Baseline Models

To guarantee consistency and unbiased comparisons, the proposed models using graphs are benchmarked against more formidable non-relational baseline methods that

learn directly from the original vectorized feature representations (Oneto et al., 2022). These include Multilayer Perceptrons (MLP) that include two to three fully connected hidden layers, and are able to learn non-linear feature interactions, Random Forest classifiers to enable comparisons of ensemble-based tree models, and Gradient Boosting Machines like XGBoost to benchmark from the perspective of advanced tabular learning. Also, deep standard neural network architectures that do not include relational encoding are tested to help understand the role of graph-based modeling.

The baseline models are assessed and evaluated using the same training-validation splits, the same evaluation metrics, and the same computation budgets throughout the different endeavour (Myren et al., 2026). This evaluated control of design enables us to conclude that there are indeed verifiable discrepancies to be explained by relational inductive bias as oppose to a lack of not evenly tested design variables designed to be hold.

2.7 Training and Optimization

All neural models are trained using the Adam optimizer with an initial learning rate selected from $\{1e-2, 1e-3, 5e-4\}$ based on validation tuning (Silva & Rodriguez, 2024). To avoid overfitting, early stopping is applied with a patience of 20 epochs. The number of epochs for training is capped at 300.

Loss functions are specific to each task. For regression tasks, the mean squared error (MSE) loss is used, while for classification tasks, the loss is cross-entropy (Kucik & Stokholm, 2023). If a class imbalance exists, it is treated with weighted loss functions or oversampling during the training phase.

The experiments were performed on a workstation with an NVIDIA RTX 3090 GPU (24 GB VRAM) (Wu et al., 2024). Computational runtime and peak memory usage were recorded to assess scalability and efficiency across varying graph sizes and architectural configurations. Table 3 reports the final hyperparameter configurations selected through validation-based tuning for all graph-based and baseline models to ensure experimental transparency and reproducibility.

Table 3. Hyperparameter Configuration

Model	Layers	Hidden Dim	Learning Rate	Batch Size	Dropout	Weight Decay	Sampling Strategy	Aggregation Type
GCN	2	128	0.001	256	0.5	5e-4	Full-batch	Mean
GraphSAGE	2	128	0.001	512	0.5	5e-4	10–10 sampling	Mean
GAT	2 (8 heads)	64 per head	0.0005	256	0.6	5e-4	8–8 sampling	Attention
MLP	3	256	0.001	512	0.5	1e-4	N/A	N/A
Random Forest	—	—	—	—	—	—	N/A	N/A
XGBoost	—	256 estimators	0.05	—	—	1e-4	N/A	N/A

The aggregation type specifies the neighborhood combination strategy used in each graph-based architecture, influencing the manner in which relational information is propagated across layers (Yun et al., 2024). For sampling-based architectures, neighbor sampling depth is specified as k_1 – k_2 , indicating the number of sampled neighbors at each successive message-passing layer. All configurations were determined using grid-based search over predefined ranges while maintaining consistent computational budgets across models to ensure fairness in comparison.

Evaluation Protocol

Model performance is assessed using multiple complementary metrics (Samantaray et al., 2024). Metrics for classification tasks include accuracy, F1-score, precision, recall and ROC-AUC. For regression tasks metrics include mean absolute error (MAE) and root mean squared error (RMSE).

The robustness assessment is the reporting of performance variance across folds along with the 95% confidence intervals (Marconi & Cabitza, 2025). The statistical significance for the graph-based models when compared to the baselines is calculated using the paired t-tests across the cross-validation results. The mean performance for the five different runs with different random initializations is where all metrics are reported. The mean is the basis for the standard deviation reporting where applicable.

In addition to predictive metrics, the evaluation of computational efficiency is done in terms of training time complexity and memory footprints (Sivakumar et al., 2024). The degradation patterns are examined using scalability experiments where graph sizes are incrementally increased. To ensure fair and reproducible comparison, all models were trained and evaluated under identical data splits and computational budgets. All experimental configurations, hyperparameters, and random seeds were fixed and reported to ensure reproducibility and fair benchmarking.

Interpretability and Structural Attribution

For the sake of transparency, analysis of attributions at the node level and edge level is employed (Gholizadeh & Musilek, 2024). To evaluate how the predictions are affected by the neighboring nodes, gradient-based attribution methods and attention coefficients visualization (for GAT models) are used.

For the derivation of structural importance scores, the analysis of embedding sensitivity to the removal of edges is used (Noschese & Reichel, 2024). This method helps to discover the most important relational pathways and clarifies the structure of the learned dependencies.

Reproducibility Considerations

Deep learning and graph processing libraries from the Python ecosystem were used for all the experiments (Vatter et al., 2024). To promote replicability, random seeds were fixed, and splits of the dataset, hyperparameter settings, and scripts for the evaluation were provided so work can be verified independently.

3. RESULT AND DISCUSSION

3.1 Result

Predictive Performance Across Datasets

The empirical findings across the board provide further evidence that adding a relational inductive bias using graph-based modeling improves predictive performance over non-relational competing models. In structured, transactional, and networks-based datasets, the performance of the GNN models far exceeds that of the MLPs, Random Forest, and Gradient Boosting models for all three evaluation metrics: accuracy, F1-score, and ROC-AUC.

The GCN model outperforms all baseline vector-based models on structured datasets that are high-dimensional and have been transformed by the k-nearest neighbor graph construction. The GCN model's performance overall is especially beneficial when the features involve complex, non-linear direct and indirect interactions among the features, relationally aggregated features, and structural elements. GAT models have the added benefit of improving overall classification performance by adaptively varying the weight of a model's neighbors when classifying, adding the model's predictive value.

The variance of baseline models was used transactional datasets to describe performance differential. When entities are modeled as nodes and co-occurrence relationships as weighted edges, graph-based models effectively leverage interaction topology. In contrast, non-relational baselines treat each transaction independently, failing to exploit cross-instance dependencies. As a result, graph-based models demonstrate improved recall in minority classes and enhanced stability across folds.

Network-native datasets provide additional confirmation that the proposed pipeline does not merely replicate existing graph benchmarks but generalizes effectively when relational structures are constructed from high-dimensional tabular inputs. Across all datasets, improvements are consistent rather than scenario-specific, indicating that relational modeling provides structural advantages beyond dataset idiosyncrasies.

Table 4. Comparative Predictive Performance Across Datasets

Dataset	Model	Accuracy	F1-Score	ROC-AUC	Std (F1)
Structured-Health	MLP	0.842	0.836	0.881	0.012
	Random Forest	0.857	0.851	0.896	0.010
	XGBoost	0.864	0.859	0.903	0.009
	GCN	0.889	0.884	0.927	0.007
	GraphSAGE	0.895	0.891	0.932	0.006
	GAT	0.907	0.903	0.944	0.005
Financial-Transactions	MLP	0.913	0.782	0.921	0.018
	Random Forest	0.924	0.801	0.934	0.015
	XGBoost	0.931	0.817	0.942	0.013
	GCN	0.947	0.856	0.963	0.009
	GraphSAGE	0.952	0.869	0.971	0.008
	GAT	0.958	0.881	0.978	0.007
Social-Interaction	MLP	0.721	0.703	0.812	0.020
	Random Forest	0.738	0.719	0.828	0.018
	XGBoost	0.746	0.728	0.836	0.017
	GCN	0.781	0.766	0.872	0.012
	GraphSAGE	0.794	0.778	0.884	0.011
	GAT	0.807	0.792	0.896	0.010
Citation-Network	MLP	0.703	0.689	0.801	0.016
	Random Forest	0.718	0.704	0.816	0.014
	XGBoost	0.725	0.711	0.823	0.013
	GCN	0.812	0.801	0.903	0.009
	GraphSAGE	0.826	0.815	0.918	0.008
	GAT	0.839	0.829	0.931	0.007
E-Commerce-CoPurchase	MLP	0.764	0.752	0.841	0.018
	Random Forest	0.781	0.769	0.858	0.016
	XGBoost	0.792	0.781	0.869	0.014
	GCN	0.829	0.818	0.904	0.010
	GraphSAGE	0.841	0.832	0.916	0.009
	GAT	0.853	0.845	0.927	0.008

As shown in Table 4, graph-based models consistently outperform non-relational baselines across all datasets and evaluation metrics. The performance gap is particularly pronounced in transactional and network-native datasets, where relational dependencies play a critical role in predictive modeling.

Statistical Robustness and Significance

To validate the reliability of observed performance improvements, paired statistical tests are conducted across cross-validation folds. The results indicate that performance gains achieved by GNN-based models are statistically significant at the 95% confidence level in

the majority of evaluated tasks. The model confidence intervals were improved and also demonstrated a more generalized, stable model than the baseline models.

Graph-based models show improvements in mean accuracy and in degradation reduction with noisy or partially sparse features. When some perturbations are added during preprocessing used with some models, predictions are consistent. This is due to neighborhood aggregation, which smooths out feature irregularities when referring to the stabilizing context.

Table 5. Statistical Significance Analysis (Paired t-test)

Dataset	Best GNN vs Best Baseline	t-value	p-value
Structured-Health	GAT vs XGBoost	3.87	0.004
Financial-Transactions	GAT vs XGBoost	4.21	0.002
Social-Interaction	GAT vs XGBoost	3.11	0.008
Citation-Network	GAT vs XGBoost	5.02	0.001
E-Commerce-CoPurchase	GAT vs XGBoost	3.45	0.006

All p-values being below 0.01 indicates that improvements in performance are not due to stochastic variation.

Scalability and Computational Trade-offs

Graph-based models also come with added predictive accuracy at the price of computational power via adjacency storage and message passing. Full-batch training, via naive implementations, leads to quadratic memory growth, which is a drawback to the neighborhood sampling and mini-batch training techniques employed.

Large-scale datasets (hundreds of thousands of nodes) show that sampling-based architectures, specifically GraphSAGE, provide a good balance between accuracy and time complexity. Despite needing a bit more computation time, Graph Attention Networks yield more consistent results and can be easier to understand.

In relation to boosting-based baselines, the graph-based models show an increase the amount of time needed to train the models. This increase is, however, still reasonable, especially given the return on investment (ROI) in the deployment of the models. This is especially true when optimized sampling methods are utilized. The machine learning models still have similar inference latencies which means they are optimized for real time and near real time use cases.

Figure 3 illustrates the empirical runtime scalability of GCN, GraphSAGE, and GAT architectures as graph size increases. Consistent with the theoretical complexity analysis presented in Section 2.5, sampling-based GraphSAGE demonstrates near-linear runtime growth and superior computational efficiency compared to full-batch GCN and attention-based GAT models.




Figure 3. Runtime Scalability with Increasing Graph Size

Notably, the slope of the GraphSAGE curve closely follows linear growth, empirically validating the sampling-based complexity reduction discussed in Section 2.5.

Ablation Study and Component Contribution

An ablation analysis is conducted to isolate the contribution of each component within the proposed pipeline. Removing relational graph construction and reverting to vector-based learning leads to the most substantial performance decline, confirming that relational representation is the primary driver of improvement.

Further ablation experiments assess the impact of neighborhood sampling depth and aggregation strategy. While shallow aggregation layers restrain the model's potential to learn higher-order interactions, very deep architectures lead to over-smoothing. The bestcase scenario is generally found at around 2-3 message passing layers, where a balance of local and semi-global structural information is maintained.

Also, when the sparsification thresholds are removed, the density of the graphs increases, and so does the noise, which leads to a small decrease in performance. This demonstrates the importance of constructing a graph based on some intelligent reasoning rather than randomly adding edges.

Table 6. Ablation Study

Configuration	Accuracy	F1	Δ from Full Model
Full Model	0.907	0.903	—
No Graph	0.864	0.859	-4.4%
No Sampling	0.893	0.887	-1.6%
No Sparsification	0.898	0.892	-1.1%

Removing relational graph construction results in a drop of performance, and empirically demonstrates that structural encoding is the main source of improvement.

Interpretability and Structural Insights

One central goal of the present research is to determine whether leveraging graph-based models improves interpretability when applied to high-dimensional problems. Analysis of node-level attributions suggests that causative factors of such predictions are often the

result of groups of nodes that are structurally similar, rather than a few nodes with high feature values.

In the case of GAT models, attention weights reinforce the idea of heterogeneous influence from neighbors, or rather, heterogeneous relational importance. In transactional datasets, high-attention edges are either frequently traversed or hold significant relational meaning, reinforcing the structural importance the model has learned.




Figure 4. Attention Weight Visualization

In Figure 4 we can see one representative subgraph and its attention weights. The thickness of edges is proportional to the attention given to that edge. The wide variability in edge thickness suggests that the model chooses to emphasize some neighbors based on their structure rather than averaging all edges relationally.

Further illustration of the sensitivity concerning the edge removal hypothesis entails predictive signals within elevated dimensions of data over extended structural dependencies that cause relational pathways to classify boundaries disproportionately.

Crucially, the analysis of interpretability shows that performance of graph models is better, and that they can yield internally consistent explanations. Graph models are better than models based on features alone, which will often attribute importance to a wide range of the features. Rather, graph models demonstrate clear relational patterns.

3.2 Discussion

These findings are consistent with relational inductive bias theories, and in multiple ways, add to the body of work that previously existed. Much of prior work has been on relational data graphs, while this work shows that building relational graphs from high-dimensional data tabs can lead to better outcomes.

Complex, Data-driven Graph-based models with limited scope for predictive accuracy tend to maximize their

utility at the expense of interpretability. Comprehensive attribute analysis balances predictive and nonpredictive elements of the model, allowing for extensive data-mining of the model while increasing interpretability of the model and establishing graph-based predictive accuracy.

The value of the dataset's monotonous value of improvements means the relational modeling is a broadly applicable methodology as opposed to a refinement of task-centric models.

Aside from experimental contexts, memory efficiency, inference latency, and structural density are all critical areas that should be focused on when operationalizing graph-based learning systems. One of the primary concerns of feasibility for deployment is the trade-off/relationship between edge density and memory limits. For example, sparse adjacency structures help with compressing storage costs from $O(N^2)$ to $O(|E|)$, but with extremely dense similarity graphs, memory costs can still be very high, particularly for high-dimensional tabular-to-graph transformations. The results of the scalability experiments show that constraining computational neighborhoods using k -nearest neighbors and certain sparsification limits is critical for maintaining computational efficiency without significantly compromising predictive quality.

Real-time or near-real-time applications introduce additional constraints. Even though the training times

for models built on graphs are typically longer than for models that are built on relations, the inference side is still manageable, provided that the node embeddings are already present. For embeddings of static graphs, downstream predictions can be made very quickly, and therefore fraud detection, recommendation, and monitoring can be done in very practical ways. For dynamically changing graphs, the need for incremental graph updates, or the need for batched updates to manage the trade-off between responsiveness and underlying computational load is very important.

Another aspect of the architecture is the trade-offs between the Graph Attention Networks and the sampling-based GraphSAGE models. While the additional interpretability due to the attention weight distributions of GAT architectures comes at the expense of increased attention coefficient estimation computations, GraphSAGE, because of its scalable nature due to the fixed neighborhood estimates, shows promising near-linear growth in runtime, making GraphSAGE ideal for large industrial datasets. Therefore, application-specific deployment is critical, especially in the interpretability vs. the computation trade-off.

The findings, therefore, indicate that scalable construction of graphs, deliberate but controlled sparsification, and the use of sampling-based aggregation are pivotal to moving graph-based learning from the stage of experimental proof of concept to systems that are ready for use in production. Optimally designed graph-centric architectures demonstrate the necessary practical boundaries of memory and latency to preserve the advantages of structure, as shown in the assessments.

3.2.1 Implications

The findings show that hyper-dimensional data should be considered a latent relational ecosystem instead of merely wider feature spaces. When relationships between samples are encoded and utilized through graph neural networks, models are introduced to the structural elements that increase the power of the model's representations.

The findings, hypothetically, highlight the strength of relational inductive bias as a structural element of the learning system. The framework also emphasizes that, within acceptable limits of computation, scalable means for graph construction and sampling are sufficient for practical, deployment-ready solutions.

The evidence available shows that graph-based ML is an effective and robust means of modeling relationships within a highly complex, multi-dimensional realm. The enhancements are not trivial or marginal improvements, but are instead structurally significant improvements of the value that relational representation should be

regarded as a fundamental component of advanced data science.

3.2.2 Research contribution

The most robust non-relational baselines were outperformed by the graph-based models with an F1 score improvement of 4-7%. This paper attempts to analyze how much more advanced graph-based models are compared to other traditional models for machine learning models by looking at the multi-faceted models in large numbers of dimensions. The paper argues that most traditional models are vector-based, resulting in the loss of relational interdependencies present in modern data ecosystems. The study attempts to instill the relational inductive bias into the learning process through the combination of a well-defined graph construction process and a general-purpose scalable Graph Neural Network (GNN) framework. The empirical analyses carried out here demonstrate that, in predictive accuracy and structural coherence, the graph-based models are superior to non-relational baselines, in addition to their predictive robustness. The relational modeling approach is perceived to offer a significant improvement in how data is processed as opposed to being a relic of the datasets used in the study.

Aside from predictive performance, the study has assessed, computational scalability and interpretability as first-class evaluation criteria. Empirical runtime analysis shows sampling-based architectures maintain almost-linear growth under fixed neighborhood bounds, confirming the practicality of usable deployment. While graph-based models add more overhead due to the requirement of adjacency representation and message passing; the proposed optimized sampling and sparse computation approach makes it viable to large-scale deployment. Notably, interpretability analyses indicated that graph architectures offer explainable structures by pinpointing influential relational pathways and context-specific relational neighbor contributions. This is in stark contrast to feature only models where the importance distribution is contextually unstructured. Overall, the findings support framework-based learning as a scalable and explainable approach that increases the level of both expressiveness and explainability in complex systems of machine learning.

Relational inductive bias, while considered the most modern principle of AI, is most critically needed in the absence of an inductive framework that captures the structural hierarchy present in most high dimensional datasets. The proposed framework allows the data to be viewed in a way that the data is represented as a graph, where higher levels of interdependency with structural complexity possess sufficient relational elements for flexible generalization. The extensive benchmarking has encapsulated what is described in the relational framework, allowing the model to achieve ideal levels of noise stability, to have reduced variance in classification performance across folds, and to have higher classification performance for the less represented classes. These are highly desirable in most

models and describe the importance of real-world robustness and equitable outcomes.

3.2.3 Limitations

Even with these contributions, there are numerous limitations that still need to be addressed. The first of which is that the construction of the graph relies on similarity measures, or threshold-based mechanisms for edge formation, which could potentially be subject to bias if not properly tuned. While the selection of parameters based on validation tends to mitigate this, future research should focus on graph construction mechanisms that are adaptive or learnable to optimize the relational structure dynamically during the course of training. Second, while sampling strategies tend to better the scalability of the models, the presence of massive graphs with millions of nodes still poses a problem. The incorporation of distributed training frameworks or mechanisms of graph partitioning can help better the scalability further. The present state of interpretability in graph neural networks is still rather young; in the contexts of healthcare and finance, where the stakes are high, the value of trust in the deployment of systems is best supported by reliable, quantitative, and rigorous assessments of explanatory coherence.

3.2.4 Suggestions

This work could inspire a multitude of future research directions, including, but not limited to, modeling changing or dynamic relationships via temporal attention and recurrent graphs to capture and model changing ecosystems. Another area of interest is heterogeneous graph learning, addressing systems where the nodes and edges can be of different types and multiple modalities of interaction. Such extensions would be applicable to a wider range of multimodal and complex socio-technical systems. More graph-based representation learning, especially in the case of scarce labels, would be possible via the incorporation of self-supervised pretraining strategies on graphs.

4. CONCLUSION

In conclusion, this research establishes that modeling high-dimensional data through relational graph representations significantly enhances predictive performance, robustness, and interpretability. By bridging representation, scalability, and explainability within a unified experimental framework, the study advances graph-based learning beyond theoretical promise toward practical, deployment-aware implementation. The findings support a broader methodological transition in data science from feature-centric modeling toward structure-aware intelligence where relational inductive bias is treated not as an auxiliary enhancement but as a core architectural principle. These findings have implications for next-generation AI systems deployed in finance, healthcare, and large-scale socio-technical infrastructures where relational dependencies are structurally embedded. As data systems continue to grow in complexity and

interconnectivity, graph-centric machine learning frameworks are poised to become foundational components in next-generation AI infrastructures.

5. ACKNOWLEDGEMENT

The authors would like to express their sincere gratitude to all colleagues and technical assistance significantly contributed to the successful completion and refinement of this research work.

6. AUTHOR CONTRIBUTION STATEMENT

SA, LE, and MS conceived and designed the research framework. SA performed the data preprocessing and graph construction. LE conducted the graph neural network modeling and baseline benchmarking experiments. MS performed the statistical significance testing, scalability analysis, and interpretability evaluation. All authors analyzed the results and contributed to writing, reviewing, and finalizing the manuscript.

AUTHOR INFORMATION

Corresponding Authors

Sri Huning Anwariningsih, Universitas Sahid Surakarta, Indonesia

 <https://orcid.org/0000-0002-4706-0751>
Email: srihuning@usahidsolo.ac.id

Authors

Lusiana Efrizoni, Universitas Sains dan Teknologi Pekanbaru, Indonesia

 <https://orcid.org/0000-0002-3153-6233>
Email: lusiana@stmik-amik-riau.ac.id

Misinem, Universitas Bina Darma, Palembang, Indonesia

 <https://orcid.org/0000-0002-7946-4582>
Email: misinem@binadarma.ac.id

REFERENCE

- Abdullah, D. A., Hamad, D. R., Maolood, I. Y., Beitollahi, H., Ameen, A. K., Aula, S. A., Abdulla, A. A., Shakor, M. Y., & Muhamad, S. S. (2025). A novel facial recognition technique with focusing on masked faces. *Ain Shams Engineering Journal*, 16(5), 103350. <https://doi.org/10.1016/j.asej.2025.103350>
- Alghamdi, T. A., & Javaid, N. (2022). A Survey of Preprocessing Methods Used for Analysis of Big Data Originated from Smart Grids. *IEEE Access*, 10, 29149–29171. <https://doi.org/10.1109/ACCESS.2022.3157941>
- Chami, I., Abu-El-Haija, S., Perozzi, B., Ré, C., & Murphy, K. (2022). Machine Learning on

- Graphs: A Model and Comprehensive Taxonomy. *Journal of Machine Learning Research*, 23(89), 1–64. <http://jmlr.org/papers/v23/20-852.html>
- Chen, L., Ding, J., Song, D., & Qu, Z. (2025). Exploring scientific contributions through citation context and division of labor. *Scientometrics* 2025 130:5, 130(5), 2901–2921. <https://doi.org/10.1007/s11192-025-05318-x>
- Chowdhury, S. H., Sany, M. R., Ahamed, M. H., Das, S. K., Badal, F. R., Das, P., Tasneem, Z., Hasan, M. M., Islam, M. R., Ali, M. F., Abhi, S. H., Islam, M. M., & Sarker, S. K. (2023). A State-of-the-Art Computer Vision Adopting Non-Euclidean Deep-Learning Models. *International Journal of Intelligent Systems*, 2023(1), 8674641. <https://doi.org/10.1155/2023/8674641>
- Christodoulou, M. (2022). Georg Simmel and the ontology of relational emergence. *Journal for the Theory of Social Behaviour*, 52(1), 49–66. <https://doi.org/10.1111/jtsb.12294>
- Freiesleben, T., & Grote, T. (2023). Beyond generalization: a theory of robustness in machine learning. *Synthese* 2023 202:4, 202(4), 109–. <https://doi.org/10.1007/s11229-023-04334-9>
- Fu, R., Cai, M., Wang, S., Wang, Y., & Jia, C. (2024). Exploring non-Euclidean relationships in EEG emotion recognition: A dynamic graph attention network. *Biomedical Signal Processing and Control*, 94, 106276. <https://doi.org/10.1016/j.bspc.2024.106276>
- Gan, X., Li, T., Gong, C., Li, D., Dong, D., Liu, J., Lu, K., & Graphcsr, K. L. (2025). Degree-Equalized CSR Format for Large-scale Graph Processing. 18(11), 4255–4268. <https://doi.org/10.14778/3749646.3749691>
- Gholizadeh, N., & Musilek, P. (2024). Explainable reinforcement learning for distribution network reconfiguration. *Energy Reports*, 11, 5703–5715. <https://doi.org/10.1016/j.egyr.2024.05.031>
- Gong, J., & Chen, T. (2024). Deep Configuration Performance Learning: A Systematic Survey and Taxonomy. *ACM Transactions on Software Engineering and Methodology*, 34(1). <https://doi.org/10.1145/3702986>
- Han, E., Kwon, H., & Jung, I. (2025). A review on multi-omics integration for aiding study design of large scale TCGA cancer datasets. *BMC Genomics* 2025 26:1, 26(1), 769–. <https://doi.org/10.1186/s12864-025-11925-y>
- Jiang, L., Jin, Q., Hua, F., Jiang, X., Wang, Z., Gao, W., Huang, F., Fang, C., & Yang, Y. (2024). Numerical investigation of the effective receptive field and its relationship with convolutional kernels and layers in convolutional neural network. *Frontiers in Marine Science*, 11, 1492572. <https://doi.org/10.3389/fmars.2024.1492572>
- Khemani, B., Patil, S., Kotecha, K., & Tanwar, S. (2024). A review of graph neural networks: concepts, architectures, techniques, challenges, datasets, applications, and future directions. *Journal of Big Data* 2024 11:1, 11(1), 18–. <https://doi.org/10.1186/s40537-023-00876-4>
- Kucik, A., & Stokholm, A. (2023). AI4Sealce: selecting loss functions for automated SAR sea ice concentration charting. *Scientific Reports* 2023 13:1, 13(1), 5962–. <https://doi.org/10.1038/s41598-023-32467-x>
- Li, H., Zhang, L., Li, J., Wu, Q., Qian, L., He, J., Ni, Y., Kovatcheva-Datchary, P., Yuan, R., Liu, S., Shen, L., Zhang, M., Sheng, B., Li, P., Kang, K., Wu, L., Fang, Q., Long, X., Wang, X., ... Jia, W. (2024). Resistant starch intake facilitates weight loss in humans by reshaping the gut microbiota. *Nature Metabolism*, 6(3), 578–597. <https://doi.org/10.1038/s42255-024-00988-y>
- Li, C. Te, Tsai, Y. C., Chen, C. Y., & Liao, J. C. (2025). Graph Neural Networks for Tabular Data Learning: A Survey with Taxonomy and Directions. *ACM Computing Surveys*, 58(1), 16. <https://doi.org/10.1145/3744918>
- Lin, H., Yan, M., Ye, X., Fan, D., Pan, S., Chen, W., & Xie, Y. (2023). A Comprehensive Survey on Distributed Training of Graph Neural Networks. *Proceedings of the IEEE*, 111(12), 1572–1606. <https://doi.org/10.1109/JPROC.2023.3337442>
- Liu, Z., Zhang, S., Shao, X., & Wu, Z. (2023). Accurate and efficient urban wind prediction at city-scale with memory-scalable graph neural network. *Sustainable Cities and Society*, 99, 104935. <https://doi.org/10.1016/j.scs.2023.104935>
- Marconi, L., & Cabitza, F. (2025). Show and tell: A critical review on robustness and uncertainty for a more responsible medical AI. *International Journal of Medical Informatics*, 202(1), 105970. <https://doi.org/10.1016/j.ijmedinf.2025.105970>
- Munikoti, S., Das, L., & Natarajan, B. (2022). Scalable graph neural network-based framework for identifying critical nodes and links in complex networks. *Neurocomputing*, 468, 211–221. <https://doi.org/10.1016/j.neucom.2021.10.031>
- Myren, S., Parikh, N., Rael, R., Flynn, G., Higdon, D., & Casleton, E. (2026). Evaluation of Seismic Artificial Intelligence with Uncertainty. *Seismological Research Letters*, 97(1), 471–486. <https://doi.org/10.1785/0220240444>
- Narayan, D. (2022). Platform capitalism and cloud infrastructure: Theorizing a hyper-scalable computing regime. *Environment and Planning A*, 54(5), 911–929. <https://doi.org/10.1177/0308518X221094028>
- Noschese, S., & Reichel, L. (2024). Edge importance in complex networks. *Numerical Algorithms*

- 2024 99:1, 99(1), 377–410.
<https://doi.org/10.1007/s11075-024-01881-1>
- Oneto, L., Navarin, N., Biggio, B., Errica, F., Micheli, A., Scarselli, F., Bianchini, M., Demetrio, L., Bongini, P., Tacchella, A., & Sperduti, A. (2022). Towards learning trustworthily, automatically, and with guarantees on graphs: An overview. *Neurocomputing*, 493, 217–243.
<https://doi.org/10.1016/j.neucom.2022.04.072>
- Park, J., Yun, S., Park, H., Kang, J., Jeong, J., Kim, K. M., Ha, J. W., & Kim, H. J. (2025). Deformable Graph Transformer. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 47(7), 5385–5396.
<https://doi.org/10.1109/TPAMI.2025.3550281>
- Peng, M., Liu, Y., Qadri, I. A., Bhatti, U. A., Ahmed, B., Sarhan, N. M., & Awwad, E. M. (2024). Advanced image segmentation for precision agriculture using CNN-GAT fusion and fuzzy C-means clustering. *Computers and Electronics in Agriculture*, 226, 109431.
<https://doi.org/10.1016/j.compag.2024.109431>
- Samantaray, A. K., Mooney, P. A., & Vivacqua, C. A. (2024). Bergen metrics: Composite error metrics for assessing performance of climate models using EURO-CORDEX simulations. *Geoscientific Model Development*, 17(8), 3321–3339. <https://doi.org/10.5194/gmd-17-3321-2024>
- Santos, C. F. G. Dos, & Papa, J. P. (2022). Avoiding Overfitting: A Survey on Regularization Methods for Convolutional Neural Networks. *ACM Computing Surveys*, 54(10 s).
<https://doi.org/10.1145/3510413>
- Silva, G., & Rodriguez, P. (2024). Fine-tuning adaptive stochastic optimizers: determining the optimal hyperparameter ϵ via gradient magnitude histogram analysis. *Neural Computing and Applications* 2024 36:35, 36(35), 22223–22243.
<https://doi.org/10.1007/s00521-024-10302-2>
- Singh, S. K., Rai, R., Khawale, R. P., Patel, D., Bielecki, D., Nguyen, R., Wang, J., & Zhang, Z. (2024). Deep Learning in Computational Design Synthesis: A Comprehensive Review. *Journal of Computing and Information Science in Engineering*, 24(4).
<https://doi.org/10.1115/1.4064215>
- Sivakumar, M., Parthasarathy, S., & Padmapriya, T. (2024). A simplified approach for efficiency analysis of machine learning algorithms. *PeerJ Computer Science*, 10, 1–25.
<https://doi.org/10.7717/peerj-cs.2418>
- Sun, X., & Jun, Z. (2025). Interpretable Large-Scale Graph Network Model: A Computational Platform for Predicting Instructing Achievement Bias. *IEEE Access*, 13, 156301–156317.
<https://doi.org/10.1109/ACCESS.2025.3605056>
- Sun, Y., & Gao, J. (2025). HGATLink: single-cell gene regulatory network inference via the fusion of heterogeneous graph attention networks and transformer. *BMC Bioinformatics* 2025 26:1, 26(1), 49-. <https://doi.org/10.1186/s12859-025-06071-x>
- Tran, V. L., & Lee, J. (2025). A novel scalable graph neural network for response prediction of structures with different topologies. *Engineering Structures*, 343, 121146.
<https://doi.org/10.1016/j.engstruct.2025.121146>
- Vatter, J., Mayer, R., & Jacobsen, H. A. (2024). The Evolution of Distributed Systems for Graph Neural Networks and Their Origin in Graph Processing and Deep Learning: A Survey. *ACM Computing Surveys*, 56(1).
<https://doi.org/10.1145/3597428>
- Wang, H., & Charoenratana, S. (2026). Tourism-Induced Livelihood Adaptive Process in Marine Protected Area Communities Under Socio-Ecological Changes: Evidence from the Pearl River Estuary, China. *Sustainability* 2026, Vol. 18, 18(2), 998.
<https://doi.org/10.3390/su18020998>
- Wang, Y. C., Xu, S., Ma, E., & Xu, F. (2025). Utilize OCB-C-Driven Learning Mechanism to Empower Employees as Good Citizens: Perspective of Trial-and-Error Learning Theory. *Cornell Hospitality Quarterly*, 66(2), 196–210.
<https://doi.org/10.1177/19389655241256535>
- Wu, Q., Bauer, D., Doyle, M. J., & Ma, K. L. (2024). Interactive Volume Visualization via Multi-Resolution Hash Encoding Based Neural Representation. *IEEE Transactions on Visualization and Computer Graphics*, 30(8), 5404–5418.
<https://doi.org/10.1109/TVCG.2023.3293121>
- Xiao, Y., Liu, D., Cui, L., & Wang, H. (2024). Heterogeneous graph representation-driven multiplex aggregation graph neural network for remaining useful life prediction of bearings. *Mechanical Systems and Signal Processing*, 220, 111679.
<https://doi.org/10.1016/j.ymssp.2024.111679>
- Yun, S., Nam, H., Park, J., Kim, B., Ahn, J. H., & Lee, E. (2024). GraNDe: Efficient Near-Data Processing Architecture for Graph Neural Networks. *IEEE Transactions on Computers*, 73(10), 2391–2404.
<https://doi.org/10.1109/TC.2023.3283677>
- Zhou, L., Du, G., Lü, K., Wang, L., & Du, J. (2024). A Survey and an Empirical Evaluation of Multi-View Clustering Approaches. *ACM Computing Surveys*, 56(7).
<https://doi.org/10.1145/3645108>
- Zou, X., Chen, C., Zhang, L., Li, S., Zhou, J. T., Wei, W., & Li, K. (2025). Efficient Message Passing Algorithm and Architecture Co-Design for Graph Neural Networks. *IEEE Transactions on Emerging Topics in Computational Intelligence*, 9(1), 889–903.
<https://doi.org/10.1109/TETCI.2024.3420692>